



Dimensionen: Blistergurt und Rolle

gemäss IEC 60286-3

Typ	P1 [mm]	F [mm]	W [mm]	N [mm]	W1 [mm]	W2 [mm]	A											
							300 Stk [mm]	500 Stk [mm]	750 Stk [mm]	1k Stk [mm]	1.5k Stk [mm]	2k Stk [mm]	3k Stk [mm]	5k Stk [mm]	6k Stk [mm]	10k Stk [mm]	15k Stk [mm]	
HCF	8	7.5	16	62	16.4	22.4	180											
HCSF	8	7.5	16	62	16.4	22.4	180											
MGA	4	3.5	8	62	8.4	14.4			180					330			330	
MGA-A	4	3.5	8	62	8.4	14.4			180					330			330	
MGA-S	4	3.5	8	62	8.4	14.4			180									
MKF	4	5.5	12	62	12.4	18.4		180					180					
MKT	4	5.5	12	62	12.4	18.4		180					180					
MSB	4	5.5	16	62	16.4	20.4							180					
OMF 63	8	7.5	16	62	16.4	22.4			180					330				
OMF 125	8	7.5	16	62	16.4	22.4			180					330				
OMF 250	8	11.5	24	62	24.4	30.4							380					
OMH 125	8	11.5	24	62	24.4	30.4			330				380					
OMK 63	8	11.5	24	62	24.4	30.4							380					
OMK 125	8	11.5	24	62	24.4	30.4			330				380					
OMT	8	11.5	24	62	24.4	30.4							330					
OMT 125	8	7.5	16	62	16.4	22.4			180					330				
OMZ 125	8	11.5	24	62	24.4	30.4			330				380					
PFDF	8	7.5	16	62	16.4	22.4											360	
PFHT	8/12	7.5	16	62	16.4	22.4							360	360				
PFMF	8	5.5	12	62	12.4	18.4							180	180				
PFNF	4	3.5	8	62	8.4	14.4								180				
PFSM	8/12	7.5	16	62	16.4	22.4							360	360				
PFUF	4	3.5	8	62	8.4	14.4								180				
RTS	12	7.5	16	62	16.4	22.4			330									
UAI 1206	4	3.5	8	62	8.4	14.4				180								
UMF 250	8	11.5	24	62	24.4	30.4							330					
UMK 250	8	11.5	24	62	24.4	30.4				330								
UMT-H	8	11.5	24	62	24.4	30.4							330					
UMT 250	8	11.5	24	62	24.4	30.4							330					
UMZ 250	8	11.5	24	62	24.4	30.4				330								
USF 0402	2	3.5	8	62	8.4	14.4											180	
USF 0603	4	3.5	8	62	8.4	14.4				180					254			330
USF 1206	4	3.5	8	62	8.4	14.4				180					254			330
USFF 12064		3.5	8	62	8.4	14.4				180					254		330	
USI 1206	4	3.5	8	62	8.4	14.4				180					254			330
USN 1206	4	3.5	8	62	8.4	14.4				180					254			330
UST 1206	4	3.5	8	62	8.4	14.4				180					254			330
172876	4	5.5	16	62	16.4	20.4							180					