

AMT PCAP Touch Screen, Adhesive / Film / Film Version, AFF															
SIZE	PART NO.:	AMT PART NO.:	ADAPTED CONTROLLER	EMC	INTERFACE	VERSION	TOTAL THICKN.	TAIL / TERM.	TAIL LENGTH	OUTSIDE AREA L*W (mm)	VIEW AREA L*W (mm)	ACTIVE AREA L*W (mm)	KEY AREA L*W (mm)	WEIGHT (g)	QTY / Box
5,7"	1060.0204	P3004-A1B	PM1210	10V	USB / RS232 / I <sup>2</sup> C / UART	AFF	0,4mm	FPC/ZIF	49,50	129.80 * 102.00	119.16 * 90.12	118.16 * 89.12	116.16 * 87.12	15	30
7" w	1060.0228	P3012-A1B	PM1210	10V	USB / RS232 / I <sup>2</sup> C / UART	AFF	0.4mm	FPC/ZIF	49,50	171.60 * 112.44	160.60 * 98.44	159.60 * 97.44	153.60 * 91.44	16	30
8.4"	1060.0230	P3007-A1A	PM1310	10V	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	191.90 * 152.30	179.40 * 136.80	178.40 * 135.80	172.40 * 129.80	30	30
10.1"w	1060.0226	P3021-A1A	PM1310	10V	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	231.96 * 154.60	223.96 * 142.60	222.96 * 141.60	216.96 * 135.60	27	30
10.4"	1060.0232	P3008-A1A	PM1310	10V	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	227.20 * 179.10	212.03 * 159.42	211.03 * 158.42	211.03 * 158.42	40	30
12.1"	1060.0244	P3026-A10	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	267.50 * 209.50	253.00 * 191.50	252.00 * 190.50	246.00 * 184.50	60	30
12.1"w	1060.0265	P3030-A10	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	277.62 * 184.70	268.12 * 170.20	267.12 * 169.20	261.12 * 163.20	65	30
15,0"	1060.0261	P3029-A10	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	322.60 * 251.10	311.10 * 235.10	310.10 * 234.10	304.10 * 228.10	60	30
15.6"w	1060.0246	P3023-A1A	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	361.73 * 216.04	351.23 * 200.54	350.23 * 199.54	344.23 * 193.54	60	30
17"	1060.0263	P3028-A10	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	360.92 * 295.34	344.90 * 277.34	343.92 * 276.34	337.92 * 270.34	90	30
18.5"w	1060.0250	P3019-A1A	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	431.60 * 253.20	414.60 * 235.20	413.60 * 234.20	409.80 * 230.40	80	30
19"	1060.0252	P3027-A10	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	401.30 * 326.10	381.30 * 306.10	380.30 * 305.10	376.30 * 301.10	95	30
21.5"w	1060.0253	P3022-A1A	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	502.20 * 295.20	484.20 * 275.70	483.20 * 274.70	477.20 * 268.70	105	30
24"w	1060.0256	P3025-A10	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	AFF	0.4 mm	FPC/ZIF	49,50	550.36 * 322.89	538.36 * 305.89	537.36 * 304.89	531.36 * 298.89	120	20
AMT PCAP Touch Screen, Glass / Film / Film Version, GFF															
SIZE	PART NO.:	AMT PART NO.:	ADAPTED CONTROLLER	EMC	INTERFACE	VERSION	TOTAL THICKN.	TAIL / TERM.	TAIL LENGTH	OUTSIDE AREA L*W (mm)	VIEW AREA L*W (mm)	ACTIVE AREA L*W (mm)	KEY AREA L*W (mm)	WEIGHT (g)	QTY / Box
5,7"	1060.0205	P3004-A2B	PM1210	10V	USB / RS232 / I <sup>2</sup> C / UART	GFF	1,5mm	FPC/ZIF	49,50	130.80 * 103.00	119.16 * 90.12	118.16 * 89.12	116.16 * 87.12	50	20
7" w	1060.0229	P3012-A2B	PM1210	10V	USB / RS232 / I <sup>2</sup> C / UART	GFF	1.5 mm	FPC/ZIF	49,50	172.60 * 113.44	160.60 * 98.44	159.60 * 97.44	153.60 * 91.44	59	20
8.4"	1060.0231	P3007-A2A	PM1310	10V	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	FPC/ZIF	49,50	192.90 * 153.30	179.40 * 136.80	178.40 * 135.80	172.40 * 129.80	83	20
10.1"w	1060.0227	P3021-A2A	PM1310	10V	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	FPC/ZIF	49,50	232.96 * 155.60	223.96 * 142.60	222.96 * 141.60	216.96 * 135.60	109	20
10.4"	1060.0233	P3008-A2A	PM1310	10V	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	FPC/ZIF	49,50	228.20 * 180.10	212.03 * 159.42	211.03 * 158.42	211.03 * 158.42	145	15
12.1"	1060.0245	P3026-A20	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	GFF	1.5 mm	FPC/ZIF	49,50	268.50 * 210.50	253.00 * 191.50	252.00 * 190.50	246.00 * 184.50	210	15
12.1"w	1060.0266	P3030-A20	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	GFF	2.2 mm	FPC/ZIF	49,50	278.62 * 185.70	268.12 * 170.20	267.12 * 169.20	261.12 * 163.20	156	20
15,0"	1060.0262	P3029-A20	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	GFF	2.2 mm	FPC/ZIF	49,50	323.60 * 252.10	311.10 * 235.10	310.10 * 234.10	304.10 * 228.10	443	15
15.6"w	1060.0247	P3023-A2A	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	GFF	2.2 mm	FPC/ZIF	49,50	362.73 * 217.04	351.23 * 200.54	350.23 * 199.54	344.23 * 193.54	406	10
17"	1060.0264	P3028-A20	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	GFF	2.2 mm	FPC/ZIF	49,50	361.92 * 296.34	344.90 * 277.34	343.92 * 276.34	337.92 * 270.34	585	12
18.5"w	1060.0251	P3019-A2A	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	GFF	2.2 mm	FPC/ZIF	49,50	432.60 * 254.20	414.60 * 235.20	413.60 * 234.20	409.80 * 230.40	565	15
19"	1060.0255	P3027-A20	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	GFF	2.2 mm	FPC/ZIF	49,50	402.30 * 327.10	381.30 * 306.10	380.30 * 305.10	376.30 * 301.10	700	10
21.5"w	1060.0254	P3022-A2A	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	GFF	2.2 mm	FPC/ZIF	49,50	503.20 * 296.20	484.20 * 275.70	483.20 * 274.70	477.20 * 268.70	763	10
24"w	1060.0257	P3025-A20	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	GFF	2.2 mm	FPC/ZIF	49,50	551.36 * 323.89	538.36 * 305.89	537.36 * 304.89	531.36 * 298.89	925	5

AMT standard PCAP Touch Screen with Decor Glass (printed frame)															
SIZE	PART NO.:	AMT PART NO.:	PENMOUNT CONTROLLER	EMC	INTERFACE	VERSION	TOTAL THICKN.	TAIL / TERM.	TAIL LENGTH	OUTSIDE AREA L*W (mm)	VIEW AREA L*W (mm)	ACTIVE AREA L*W (mm)	KEY AREA L*W (mm)	WEIGHT (g)	QTY / Box
4.3"	1060.0306	P3015-CG0 (P2-02)	PM2101 (COF)	N/A	USB / I <sup>2</sup> C / UART	DFF	1.5 mm	COF	55,00	121.10 * 85.90	97.10 * 55.90	99.10 * 57.90	96.10 * 54.90	35	7
4.3"	1060.0307	P3015-CGA (P2-03)	PM2102 (COF)	N/A	USB / I <sup>2</sup> C / UART	DFF	1.5 mm	COF	55,00	121.10 * 85.90	97.10 * 55.90	99.10 * 57.90	96.10 * 54.90	35	7
7.0" w	1060.0300	P3012-CGA (P2-03)	PM2201(COF)	N/A	USB / I <sup>2</sup> C / UART	DFF	1.5 mm	COF	69,50	186.60 * 131.00	154.60 * 91.44	159.08 * 97.44	153.60 * 91.44	90	7
7.0" w	1060.0332	P3012-CGD (P2-06)	PM2203B (COF)	10V	USB / I <sup>2</sup> C / UART	DFF	1.5 mm	COF	69,50	186.60 * 131.00	154.60 * 91.44	159.08 * 97.44	153.60 * 91.44	90	7
7.0" w	1060.0317	P3012-AGB	PM1210	10V	USB / RS232 / I <sup>2</sup> C / UART	DFF	1.5 mm	FPC/ZIF	49,50	186.60 * 131.00	154.60 * 92.44	159.60 * 97.44	153.60 * 91.44	79	7
10.1"	1060.0308	P3021-CGA	PM2300(COF)	10V	USB / I <sup>2</sup> C / UART	DFF	1.5 mm	COF	79,50	249.96 * 176.60	217.56 * 136.20	222.96 * 141.60	216.96 * 135.60	155	7
10.1"	1060.0326	P3021-AGA	PM1310	10V	USB / I <sup>2</sup> C / UART	DFF	1.5 mm	FPC/ZIF	49,50	249.96 * 176.60	217.56 * 136.20	222.96 * 141.60	216.96 * 135.60	136	7
10.4"	1060.0309	P3008-AGA	PM1310	10V	USB / I <sup>2</sup> C / UART	DFF	1,5 mm	FPC/ZIF	49,50	251.03 * 202.42	211.03 * 158.42	211.03 * 158.42	211.03 * 158.42	170	15
10.4"	1060.0330	P3024-CG0	PM2300(COF)	10V	USB / I <sup>2</sup> C / UART	DFF	1.5 mm	COF	79,50	251.03 * 202.42	211.03 * 158.42	216.03 * 163.42	211.03 * 158.42	175	7
12.1"w	1060.0327	P3026-AG0	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	DFF	2,2 mm	FPC/ZIF	49,50	295.00 * 239.50	247.00 * 185.50	252.00 * 190.50	246.00 * 184.50	355	7
15.0"	1060.0328	P3029-AG0	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	DFF	2.2 mm	FPC/ZIF	49,50	357.10 * 289.10	305.10 * 229.10	310.10 * 234.10	304.10 * 228.10	525	12
15.6"w	1060.0325	P3023-AGA	PM1410	10V	USB / RS232 / I <sup>2</sup> C / UART	DFF	2,2 mm	FPC/ZIF	49,50	395.23 * 258.54	345.23 * 194.54	350.23 * 199.54	344.23 * 193.54	451	10
17"	1060.0329	P3028-AG0	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	DFF	2,2 mm	FPC/ZIF	49,50	390.92 * 323.34	338.92 * 271.34	343.92 * 276.34	337.92 * 270.34	713	12
18.5"w	1060.0321	P3019-AGA	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	DFF	2,2 mm	FPC/ZIF	49,50	464.80 * 285.40	410.40 * 231.00	413.60 * 234.20	409.80 * 230.40	680	12
21.5"w	1060.0322	P3022-AGA	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	DFF	2.2 mm	FPC/ZIF	49,50	538.20 * 329.70	478.20 * 269.70	483.20 * 274.70	477.20 * 268.70	843	7
24"w	1060.0323	P3025-AG0	PM1710 / 1711	10V	USB / RS232 USB / I <sup>2</sup> C / UART	DFF	2.2 mm	FPC/ZIF	49,50	577.76 * 360.29	531.96 * 299.49	537.36 * 304.89	531.36 * 298.89	1005	10

Request glass tooling

PCAP Touch Screen with Chip on Flex, Adhesive Film Version															
SIZE	PART NO.:	AMT PART NO.:	PENMOUNT CONTROLLER	EMC	INTERFACE	VERSION	TOTAL THICKN.	TAIL / TERM.	TAIL LENGTH	OUTSIDE AREA L*W (mm)	VIEW AREA L*W (mm)	ACTIVE AREA L*W (mm)	KEY AREA L*W (mm)	WEIGHT (g)	QTY / Box
3.5"	1060.0102	P3001-C10 (P2-02)	PM2101 (COF)	N/A	I <sup>2</sup> C / UART	AFF	0.4 mm	COF	54,50	86.10 * 70.16	76.60 * 57.16	75.60 * 56.16	72.60 * 53.16	8	20
4.3"w	1060.0104	P3015-C10 (P2-02)	PM2101 (COF)	N/A	I <sup>2</sup> C / UART	AFF	0.4 mm	COF	54,50	109.60 * 71.90	100.10 * 58.90	99.10 * 57.90	96.10 * 54.90	8	20
4.3"w	1060.0114	P3015-C1A (P2-03)	PM2102 (COF)	N/A	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	COF	54,50	109.60 * 71.90	100.10 * 58.90	99.10 * 57.90	96.10 * 54.90	8	20
4.3"w	1060.0122	P3015-C1B (P2-06)	PM2103 (COF)	10V	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	COF	54,50	109.60 * 71.90	100.10 * 58.90	99.10 * 57.90	96.10 * 54.90	8	20
5.7"	1060.0106	P3010-C10 (P2-03)	PM2201 (COF)	N/A	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	COF	69,50	135.16 * 109.12	123.16 * 94.12	122.16 * 93.12	116.16 * 87.12	13	20
6.4"	1060.0108	P3011-C10 (P2-03)	PM2201 (COF)	N/A	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	COF	69,50	152.08 * 121.96	140.08 * 106.96	139.08 * 105.96	133.08 * 99.96	20	20
7.0"w	1060.0110	P3012-C1A (P2-03)	PM2201 (COF)	N/A	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	COF	69,50	171.60 * 112.44	160.60 * 98.44	159.08 * 97.44	153.60 * 91.44	15	20
7.0"w	1060.0118	P3012-C1D (P2-06)	PM2203B (COF)	10V	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	COF	69,50	171.60 * 112.44	160.60 * 98.44	159.08 * 97.44	153.60 * 91.44	15	20
10,1"w	1060.0112	P3021-C1A	PM2300 (COF)	10V	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	COF	79,50	231.96 * 154.60	223.96 * 142.60	222.96 * 141.60	216.96 * 135.60	33	20
10,4"	1060.0116	P3024-C10	PM2300 (COF)	10V	USB / I <sup>2</sup> C / UART	AFF	0.4 mm	COF	79,50	226.12 * 177.66	217.03 * 164.42	216.03 * 163.42	211.03 * 158.42	45	20

= MOQ 500 pcs.

PCAP Touch Screen with Chip on Flex, Glass Film Version															
SIZE	PART NO.:	AMT PART NO.:	PENMOUNT CONTROLLER	EMC	INTERFACE	VERSION	TOTAL THICKN.	TAIL / TERM.	TAIL LENGTH	OUTSIDE AREA L*W (mm)	VIEW AREA L*W (mm)	ACTIVE AREA L*W (mm)	KEY AREA L*W (mm)	WEIGHT (g)	QTY / Box
3.5"	1060.0103	P3001-C20	PM2101 (COF)	N/A	I <sup>2</sup> C / UART	GFF	1.5 mm	COF	54,50	87.10 * 71.16	76.60 * 57.16	75.60 * 56.16	72.60 * 53.16	22	7
4.3"w	1060.0105	P3015-C20	PM2101 (COF)	N/A	I <sup>2</sup> C / UART	GFF	1.5 mm	COF	54,50	110.60 * 72.90	100.10 * 58.90	99.10 * 57.90	96.10 * 54.90	30	7
4.3"w	1060.0115	P3015-C2A	PM2102 (COF)	N/A	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	COF	54,50	110.60 * 72.90	100.10 * 58.90	99.10 * 57.90	96.10 * 54.90	30	7
4.3"w	1060.0123	P3015-C2B	PM2103 (COF)	10V	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	COF	54,50	110.60 * 72.90	100.10 * 58.90	99.10 * 57.90	96.10 * 54.90	30	7
5.7"	1060.0107	P3010-C20	PM2201 (COF)	N/A	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	COF	69,50	136.16 * 110.12	123.16 * 94.12	122.16 * 93.12	116.16 * 87.12	55	7
6.4"	1060.0109	P3011-C20	PM2201 (COF)	N/A	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	COF	69,50	153.08 * 122.96	140.08 * 106.96	139.08 * 105.96	133.08 * 99.96	70	7
7.0"w	1060.0111	P3012-C2A (P2-03)	PM2201 (COF)	N/A	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	COF	69,50	172.60 * 113.44	160.60 * 98.44	159.08 * 97.44	153.60 * 91.44	70	7
7.0"w	1060.0119	P3012-C2D (P2-06)	PM2203B (COF)	10V	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	COF	69,50	172.60 * 113.44	160.60 * 98.44	159.08 * 97.44	153.60 * 91.44	70	7
10,1"w	1060.0113	P3021-C2A	PM2300 (COF)	10V	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	COF	79,50	232.96 * 155.60	223.96 * 142.60	222.96 * 141.60	216.96 * 135.60	128	7
10,4"	1060.0117	P3024-C20	PM2300 (COF)	10V	USB / I <sup>2</sup> C / UART	GFF	1.5 mm	COF	79,50	227.12 * 178.66	217.03 * 164.42	216.03 * 163.42	211.03 * 158.42	165	7

= MOQ 500 pcs.

PenMount Control Board			
Size	Part No.:	PenMount No.:	Interface
5.0" - 7.9"	1058.6023	PM1210	USB / RS232 / I <sup>2</sup> C / UART
8.0" - 10.5"	1058.6020	PM1310	USB / I <sup>2</sup> C / UART
10.5 - 15.6"	1058.6022	PM1410	USB / RS232 / I <sup>2</sup> C / UART
10.5 - 15.6"	1058.6033	PM1410i	I <sup>2</sup> C
10.5 - 15.6"	1058.6034	PM1410U	USB
15,6" - 24"	1058.6025	PM1710	USB / RS232
15,6" - 24"	1058.6026	PM1711	USB / I <sup>2</sup> C / UART
15,6" - 24"	1058.6035	PM1715i	I <sup>2</sup> C
15,6" - 24"	1058.6036	PM1715U	USB
Bridge Board	1058.6030	PMT101A	94-4101A-000
COF USB Converter Board	1058.6031	PMT102	94-41020-000
Cable for Board			
Cable	Part No.:	PenMount No.:	
RS232 cable mini	1058.6003	94-52014-000	
SPI/I <sup>2</sup> C cable	1058.6004	94-56002-000	
USB cable grounded	1058.6005	94-53018-000	