

Power Cord with Special Plug and Connector, Straight



Description

Power Cord,
- Protection class II, Pin temperature 70 °C, Cable

Weblinks

[pdf](#), [html](#), [General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Accessories](#), [Detailed request for product](#)

Technical Data

Dielectric Strength	> 2 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 2 acc. to IEC 61140
Terminal	moulded
Material: Housing	PVC, black or grey

Config. Code

5025 - R - Type - D - Length

The characters are placeholders for the correspondingly keys of selections from the key tables.
Typ steht für die Dose bzw. 2. Seite, Länge ist die Leitungslänge in mm.

5025 - **R** - Type - D - Length = cord type

cord type	Configuration key
special cord	Z

Cord definition is detailed in general product information XXX

5025 - R - Type - D - **Length** = Cord length

Cord length
zzzz

Cord length in mm

5025 - R - **Type** - D - Length = Cord end 2

Cord end 2
zzzz

5025 - R - Type - **D** - Length = Color

Color	Configuration key
Black	A